

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: HOFTRONIC

Supplier's address: HOF Trading Support, Fahrenheitstraat 11, 6003 DC Weert Limburg, NL

Model identifier: 5449796

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	Integrated LEDs		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	12	Energy efficiency class	D
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1 550 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode power (P_{on}), expressed in W	10,5	Standby power (P_{sb}), expressed in W and rounded to the second decimal	-
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	83
Outer dimensions without separate control gear, lighting control	Height	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width		
	Depth		

parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,446 0,407	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	5	Survival factor	-	
the lumen maintenance factor	-			

(a) : not applicable;

(b) : not applicable;

MS-FKD3B11C-V2.0 3000KChromaticity coordinates: $x=0.4460$ $y=0.4076$ $u(u')=0.2549$ $v=0.3494$ $v'=0.5241$ CCT: $T_c=2880K$ ($duv=0.00022$)Color Ratio: $R=0.239$ $G=0.738$ $B=0.023$

Peak Wavelength: 605.6nm


Half Bandwidth: 118.1nm

Dominant Wavelength: 583.3nm

Color Purity: 0.562

Central Wave: 595.8nm

Gravity Wave: 599.2nm

CRI: $R_a=83.0$ TM30: $R_f=85$, $R_g=97$ GAI: $GAI_BB_8=93.6$, $GAI_BB_15=99.7$, $GAI_EES=50.5$ $R1=81$ $R2=91$ $R3=97$ $R4=83$ $R5=83$ $R6=91$ $R7=81$ $R8=58$ $R9=5$ $R10=80$ $R11=83$ $R12=75$ $R13=84$ $R14=99$ $R15=73$ Color Quality Scale: $Q_a=83.0$, $Q_f=84.8$, $Q_p=84.3$, $Q_g=91.6$ $Q1=77$ $Q2=95$ $Q3=85$ $Q4=83$ $Q5=85$ $Q6=85$ $Q7=84$ $Q8=87$ $Q9=95$ $Q10=90$ $Q11=88$ $Q12=85$ $Q13=83$ $Q14=71$ $Q15=73$ **Photometric Parameters**

Luminous Flux: 1663.7 lm

Efficiency: 162.02 lm/W

Radiant Power: 4.955 W

Total mains efficacy: 162.02 lm/W Energy Efficiency Class: C (EU 2019/2015)

Electric Parameters

Voltage: 34.227V


Current: 0.3000A

Power: 10.27W

Power Factor: 1.0000

Frequency: 0.00Hz

Model placed on the Union market from 17/03/2023



EPREL registration number: 1528108

<https://eprel.ec.europa.eu/qr/1528108>

Supplier: HOF Trading B.V. (Manufacturer)

Website:

Customer care service:

Name: HOF Trading Support

Website: www.hoftronic.com

Email: info@hoftrading.com

Phone: +31 (0)85 401 0382

Address:

Fahrenheitstraat 11
6003 DC Weert
Netherlands