

HOFTRONIC™

DATASHEET IP66 LED FIXTURES 120CM

F-SERIES F01



Specifications

SKU
5430008

Input power	200-240V AC
Watts	25/30/35/40 Watt (Adjustable)
Equivalent watts	200 Watt
Luminous flux	5200 Lumen
Light color	Warm white, Neutral white & Daylight white
Color temperature	3000K/4000K/5000K (Adjustable)
Color rendering index (CRI)	>80
Beam angle	120°
Powerfactor	>0.92
Energy label	A++
IP-rate	IP66
Dimmable	No
Material	Polycarbonate
Dimensions	1190 x 95 x 75 mm
Operation temperature	-20°C - 45°C
Switching cycles	50.000 cycles
Life span	50.000 hours
Certification	CE, RoHS, D-MARK, SAA
Warranty	3 years
EAN	8720365430008



HOFTRONIC™

DATASHEET IP66 LED FIXTURES 120CM

F-SERIES F02 SENSOR



Specifications

SKU
5430015

Input power	200-240V AC
Watts	25/30/35/40 Watt (Adjustable)
Equivalent watts	200 Watt
Luminous flux	5200 Lumen
Light color	Warm white, Neutral white & Daylight white
Color temperature	3000K/4000K/5000K (Adjustable)
Color rendering index (CRI)	>80
Beam angle	120°
Powerfactor	>0.92
Energy label	A++
IP-rate	IP66
Dimmable	No
Material	Polycarbonate
Dimensions	1190 x 95 x 75 mm
Operation temperature	-20°C - 45°C
Switching cycles	50.000 cycles
Life span	50.000 hours
Certification	CE, RoHS, D-MARK, SAA
Warranty	3 years
EAN	8720365430015



HOFTRONIC™

DATASHEET IP66 LED FIXTURES 150CM

F-SERIES F03



Specifications

SKU
5430022

Input power	200-240V AC
Watts	35/40/50/60 Watt (Adjustable)
Equivalent watts	300 Watt
Luminous flux	7800 Lumen
Light color	Warm white, Neutral white & Daylight white
Color temperature	3000K/4000K/5000K (Adjustable)
Color rendering index (CRI)	>80
Beam angle	120°
Powerfactor	>0.92
Energy label	A++
IP-rate	IP66
Dimmable	No
Material	Polycarbonate
Dimensions	1490 x 95 x 75 mm
Operation temperature	-20°C - 45°C
Switching cycles	50.000 cycles
Life span	50.000 hours
Certification	CE, RoHS, D-MARK, SAA
Warranty	3 years
EAN	8720365430022



HOFTRONIC™

DATASHEET IP66 LED FIXTURES 150CM

F-SERIES F04 SENSOR



Specifications

SKU
5430039

Input power	200-240V AC
Watts	35/40/50/60 Watt (Adjustable)
Equivalent watts	300 Watt
Luminous flux	7800 Lumen
Light color	Warm white, Neutral white & Daylight white
Color temperature	3000K/4000K/5000K (Adjustable)
Color rendering index (CRI)	>80
Beam angle	120°
Powerfactor	>0.92
Energy label	A++
IP-rate	IP66
Dimmable	No
Material	Polycarbonate
Dimensions	1490 x 95 x 75 mm
Operation temperature	-20°C - 45°C
Switching cycles	50.000 cycles
Life span	50.000 hours
Certification	CE, RoHS, D-MARK, SAA
Warranty	3 years
EAN	8720365430039

