HOFTRONIC™

DATASHEET LED T8 ALU TUBES 60CM

160 LM/WATT

Specifications

	SKU 416468	SKU 416451	SKU 416444
Input power	100-240V AC	100-240V AC	100-240V AC
Watts	9 Watt	9 Watt	9 Watt
Equivalent watts	36 Watt	36 Watt	36 Watt
Luminous flux	1440 Lumen	1440 Lumen	1440 Lumen
Light color	Daylight white	Neutral white	Warm white
Color temperature	6000K	4000K	3000K
Color rendering index (CRI)	>80	>80	>80
Beam angle	140°	140°	140°
Powerfactor	>0.95	>0.95	>0.95
Energy label	A++	A++	A++
IP-rate	IP20	IP20	IP20
Dimmable	No	No	No
Material	Aluminum, Polycarbonate	Aluminum, Polycarbonate	Aluminum, Polycarbonate
Dimensions	588 x 26 mm	588 x 26 mm	588 x 26 mm
Operation temperature	-25°C ~ 50°C	-25°C ~ 50°C	-25°C ~ 50°C
Switching cycles	100.000 cycles	100.000 cycles	100.000 cycles
Life span	50.000 hours	50.000 hours	50.000 hours
Certification	CE, EMC, RoHS, TÜV, LM80	CE, EMC, RoHS, TÜV, LM80	CE, EMC, RoHS, TÜV, LM80
Warranty	5 years	5 years	5 years
EAN	7439628416468	7439628416451	7439628416444

Subject to changes without notice and errors. Please ensure that you always use the latest version.
©2021 HOF Trading B.V. | Fahrenheitstraat 11, 6003 DC Weert | The Netherlands. All rights reserved.

HOFTRONIC™

DATASHEET LED T8 ALU TUBES 120CM

160 LM/WATT

Specifications

	SKU 417427	SKU 417410	SKU 417403
Input power	100-240V AC	100-240V AC	100-240V AC
Watts	18 Watt	18 Watt	18 Watt
Equivalent watts	72 Watt	72 Watt	72 Watt
Luminous flux	2880 Lumen	2880 Lumen	2880 Lumen
Light color	Daylight white	Neutral white	Warm white
Color temperature	6000K	4000K	3000K
Color rendering index (CRI)	>80	>80	>80
Beam angle	140°	140°	140°
Powerfactor	>0.95	>0.95	>0.95
Energy label	A++	A++	A++
IP-rate	IP20	IP20	IP20
Dimmable	No	No	No
Material	Aluminum, Polycarbonate	Aluminum, Polycarbonate	Aluminum, Polycarbonate
Dimensions	1198 x 26 mm	1198 x 26 mm	1198 x 26 mm
Operation temperature	-25°C ~ 50°C	-25°C ~ 50°C	-25°C ~ 50°C
Switching cycles	100.000 cycles	100.000 cycles	100.000 cycles
Life span	50.000 hours	50.000 hours	50.000 hours
Certification	CE, EMC, RoHS, TÜV, LM80	CE, EMC, RoHS, TÜV, LM80	CE, EMC, RoHS, TÜV, LM80
Warranty	5 years	5 years	5 years
EAN	7439628417427	7439628417410	7439628417403

Subject to changes without notice and errors. Please ensure that you always use the latest version.
©2021 HOF Trading B.V. | Fahrenheitstraat 11, 6003 DC Weert | The Netherlands. All rights reserved.

HOFTRONIC™

DATASHEET LED T8 ALU TUBES 150CM

160 LM/WATT

Specifications

	SKU 417458	SKU 417441	SKU 417434
Input power	100-240V AC	100-240V AC	100-240V AC
Watts	30 Watt	30 Watt	30 Watt
Equivalent watts	120 Watt	120 Watt	120 Watt
Luminous flux	4800 Lumen	4800 Lumen	4800 Lumen
Light color	Daylight white	Neutral white	Warm white
Color temperature	6000K	4000K	3000K
Color rendering index (CRI)	>80	>80	>80
Beam angle	140°	140°	140°
Powerfactor	>0.95	>0.95	>0.95
Energy label	A++	A++	A++
IP-rate	IP20	IP20	IP20
Dimmable	No	No	No
Material	Aluminum, Polycarbonate	Aluminum, Polycarbonate	Aluminum, Polycarbonate
Dimensions	1498 x 26 mm	1498 x 26 mm	1498 x 26 mm
Operation temperature	-25°C ~ 50°C	-25°C ~ 50°C	-25°C ~ 50°C
Switching cycles	100.000 cycles	100.000 cycles	100.000 cycles
Life span	50.000 hours	50.000 hours	50.000 hours
Certification	CE, EMC, RoHS, TÜV, LM80	CE, EMC, RoHS, TÜV, LM80	CE, EMC, RoHS, TÜV, LM80
Warranty	5 years	5 years	5 years
EAN	7439628417458	7439628417441	7439628417434

Subject to changes without notice and errors. Please ensure that you always use the latest version.
©2021 HOF Trading B.V. | Fahrenheitstraat 11, 6003 DC Weert | The Netherlands. All rights reserved.